

Manufacturer:

OGNIOCHRON S.A.

ul. Przemysłowa 42, 34-120 Andrychów, Poland  
tel.: +48 33 875 10 70 ext. 161, e-mail: export@ogniochron.eu

www.ogniochron.eu

# ogniochron

## Application

Movable extinguishers AP-50x ABC find particular application in petrol stations, paper-mills, plastic processing and textile production plants, sawmills, furniture manufacturing plants etc.



## Basic features

- Easy and ergonomic operation.
- Quick and efficient extinguishing.
- Cut-off valve with pressure indicator makes checking of fire extinguisher easier.
- Construction of horn enables temporary interruption of extinguishing.
- Valve equipped with pressure safety plate.
- Possibility of multiple refilling.
- Deep drawn steel cylinder, painted with polyester paint resistant to UV radiation.
- 5 m long rubber hose with a horn on its end, enabling proper directing of extinguishing agent.


## Quality and safety

Manufactured according to requirements of domestic and EU markets on the basis of certified quality system ISO 9001. Fulfills requirements of European Standard EN3 and Safety Directive PED 2014/68/UE.



## Technical data

Extinguishing efficiency	A IIIB C
Weight of extinguishing agent	50 kg
Working agent	N <sub>2</sub>
Cylinder test pressure	31 bar
Operation pressure	16 bar
Operating temperature	-30 °C/+60 °C
Total weight	~85 kg
Fire under voltage	1000 V or 245000 V*
Total height (A)	1100 mm
Cylinder diameter (B)	540 mm



## Movable extinguisher 50 kg

# AP-50x ABC

