

Manufacturer:

OGNIOCHRON S.A.

ul. Przemysłowa 42, 34-120 Andrychów, Poland
tel.: +48 33 875 10 70 ext. 161, e-mail: export@ogniochron.eu

www.ogniochron.eu

ogniochron

Application

Designed for protection of community buildings, office rooms, production facilities, warehouses for flammable liquids, airports.

FF fire extinguishers contain a new type of extinguishing foam without fluorine and PFAS, making them completely biodegradable and environmentally neutral.



Basic features

- Easy and ergonomic in operation.
- Fast and effective in extinguishing.
- Economical maintenance and service.
- Cut-off valve behind the pressure indicator makes control of fire extinguisher easier.
- Construction of the valve enables temporary interruption of extinguishing.
- Possibility of multiple refilling.
- Cylinder of fire extinguisher covered with polyester paint, resistant to UV radiation.
- Interior of cylinder protected with anticorrosive layer.


Quality and safety

Manufactured according to requirements of domestic and EU markets on the basis of certified quality system ISO 9001. Fulfills requirements of European Standard EN3 and Safety Directive PED 2014/68/UE.



Technical data

Extinguishing efficiency	34A 183B
Weight of extinguishing agent	9 l
Working agent	N ₂
Operation time	min. 15 s
Cylinder test pressure	27 bar
Operation pressure	15 bar
Operating temperature	0 °C/+60 °C
Total weight	~14 kg
Fire under voltage	1000 V
Total height (A)	576 mm
Cylinder diameter (B)	185 mm



Fluorine-free foam extinguisher

GPN-9x AB/FF

FLUORINE FREE

